

## 845GV-3ISA ver 1.0

<b>Processor</b>	Socket 478 for Celeron <sup>®</sup> 4 /Pentium <sup>®</sup> 4
	FSB 533
<b>Chipset</b>	Intel <sup>®</sup> 845GV+ ICH*4
<b>Memory</b>	2 x 184-pin DDR 266/333 DIMM max.up to 2GB
<b>Ethernet</b>	Realtek RTL8100C Fast Ethernet controllers
<b>VGA</b>	Onboard VGA
<b>Expansion</b>	2*PCI slot
	1*AGP 4/8X
	3*ISA
<b>Audio</b>	Realtek ALC655 AC'97 Codec Audio
<b>Storage</b>	1*FDD
	2*IDE
<b>Back I/O Interface</b>	1*Keyboard interface
	1*Mouse interface
	4*USB
	1* COM
	1*VGA Port
	1* PRN Interface
	1*Audio interface(MIC, line out, line in)
	1* RJ45 LAN port
<b>Internal I/O interface</b>	1* Fpanel
	1* COM port
	1*Front Audio
	1* CD-IN
	1*CPUFAN interface and 1*SYSFAN interface
	1*IrDA
	2*USB
	1* 20 PIN Power interface
<b>Accessories</b>	1 x 40 pin IDE cable
	1 x FDD cable
	1 x I/O shield
<b>BIOS</b>	Award BIOS with 4Mbit Flash ROM
	Supports Plug and Play 1.0B,APM 1.2, Multi Boot, DMI
<b>Power Type</b>	ATX Input
<b>Operation Temp</b>	-10 C-60 C
<b>Operation Humidity</b>	10%~90% relative humidity, non-condensing
<b>Size</b>	293 x 180 mm,ATX

ROBY TECHNOLOGY CO., LIMITED

<https://www.chinaroby.com>

Email : gery668@hotmail.com

Skype : gery668

