

V8601T-ISA ver 1.0

| | |
|-------------------------------|---|
| Processor | Socket 370 Intel Pentium 3,Celeron 2/3 CPU,max 1.3GHz |
| | FSB 66/100/133 MHZ |
| Chipset | VIA 8601(NB), VIA8606(SB) |
| Memory | 2*168pin DIMM,SD-RAM 100/133 max.up to 512MB |
| Ethernet | NONE |
| VGA | Onbaord VGA |
| Expansion | 3*PCI slot |
| | 1*ISA |
| Audio | Realtek AC'97 AUDIO |
| Storage | 1*FDD |
| | 2*UltraDMA 133/100/66/33 |
| Back I/O Interface | 1*Keyboard interface |
| | 1*Mouse interface |
| | 2*USB 1.0 |
| | 1*VGA port |
| | 1* COM |
| | 1* PRN Interface |
| | 1*Audio interface(MIC, line out, line in) |
| Internal I/O interface | 1* Fpanel |
| | 1* CD-IN |
| | 2*USB 1.0 |
| | 1*CPUFAN interface and 1*SYSFAN interface |
| | 1* 20 PIN Power interface |
| Accessories | 1 x 40 pin IDE cable |
| | 1 x FDD cable |
| | 1 x I/O shield |
| BIOS | AMI 2Mb Flash ROM |
| | Supports Plug and Play 1.0B,APM 1.2, Multi Boot, DMI |
| Power Type | ATX Input |
| Operation Temp | -10 C-60 C |
| Operation Humidity | 10%~90% relative humidity, non-condensing |
| Size | 192 mm(W) X 244 mm (L) ,Micro ATX form factor |

ROBY TECHNOLOGY CO., LIMITED

<https://www.chinaroby.com>

Email : gery668@hotmail.com

Skype : gery668